

DRY STEAM GENERATOR WITH DIESEL OIL FIRED STEAM BOILER

- Car washes & Detail shops
- Auto dealerships
- Fleet Companies
- Rent a Car Companies
- Industrial environments in general
- Transportation



The DI series steam generators are ideal for mobile applications where high power electrical supply is not available.

	measure units	DI40	DI40 120V	DI40 12V
product code		085006947	Q80001701	Q80003137
power supply	V-Hz	230-50	120 V	12 V
total power	kW	0,4	0,4	0,4
steam production	g/min	600	600	600
steam output regulation	type	no	no	no
working pressure	bar/psi	9/131	9/131	9/131
steam temperature in boiler	°C/°F	180/356	180/356	180/356
water output regulation	yes/no	no	no	no
water output	yes/no	no	no	no
detergent output	yes/no	no	no	no
water tank capacity	liter/gallon	27/7,13	27/7,13	optional 30/7,93
unlimited autonomy	yes/no	yes	yes	yes
detergent tank capacity	liter/gallon	no	no	no
machine body material	type	abs	abs	abs
weight net	kg/lbs	110/243	110/243	110/243
machine dimension	l x p x hcm	70x106x102	70x106x102	70x106x102
packaging dimension	l x p x hcm	80x120x105	80x120x105	80x120x105
packaging weight	kg/lbs	160/352	160/352	160/352
packaging box	type	board	board	board
waste water tank capacity	liter/gallon	-	-	-
vacuum power	kW	-	-	-
vacuum	kPA	-	-	-
vacuum filter	type	-	-	-
wet & dry	yes/no	-	-	-
diesel consumption	liter/hour gallon/hour	3,4 0,89	3,4 0,89	3,4 0,89
diesel tank capacity	liter/gallon	20/5,29	20/5,29	20/5,29

leader in **dry steam** technology



The DI40 12V version is powered by a 12V DC source. Ideal for mobile applications (connects to a 12 VDC car battery of at least 100 Ah - not included). Optional 30 liter external water tank.



Imported and Distributed by:



MATHIA Trading and General Cleaning Services

Headquarters: L1 B7 Dorgali St. – Pallas Athena Classique – Anabu IID - Cavite 4103 – Philippines

Tel: +63 46 418 4751 – Mobile: +63 917 507 9888

info@mathiatrading.com • www.mathiatrading.com