

Steam master 30 kW

INDUSTRIAL STEAM GENERATOR



leader in **dry steam** technology

- Food Industry
- Beverage Industry
- Packing and Canning Industry

Steam master 30 kW SH

1 output at 11 bar with
detergent pump



Steam master 30 kW

1 output at 11 bar



Steam master 30 kW		
code	Volt -Hz	A
080006151	400-50 3 phases	44
Q80002106	400-60 3 phases	44
Q80001886	440-60 3 phases	40
Q80001809	575-60 3 phases	30

Steam master 30 kW SH		
code	Volt -Hz	A
080006154	400-50 3 phases	44
Q80002107	400-60 3 phases	44
Q80001880	440-60 3 phases	40
Q80001697	575-60 3 phases	30

	measure units	Steam master 30 kW	Steam master 30 kW SH
start up time	min	5,5	5,5
boiler capacity	liter/gallon	16/4,23	16/4,23
boiler material	type	AISI 304	AISI 304
boiler power	kW	30	30
boiler temperature regulation	yes/no	yes	yes
steam production	g/min	680	680
steam output regulation	type	manual	manual
working pressure	bar/psi	11/160	11/160
steam temperature in boiler	°C/°F	190/374	190/374
water output regulation	yes/no	no	no
water output	yes/no	yes	no
detergent output	yes/no	no	yes
water tank capacity	liter/gallon	25/6,60	25/6,60
unlimited autonomy	yes/no	yes	yes
detergent tank capacity	liter/gallon	5/1,32	5/1,32
machine body material	type	inox	inox
weight net	kg/lbs	124,5/274	124,5/274
machine dimension	l x p x h cm	95x49x97	95x49x97
packaging dimension	l x p x h cm	115x61x115	115x61x115
packaging weight	kg/lbs	168,5/372	168,5/372
packaging box	type	wooden	wooden
vacuum cleaner	yes/no/optional	optional	optional
waste water tank capacity	liter/gallon	-	-
vacuum power	kW	-	-
vacuum	kPA	-	-
vacuum filter	type	-	-
wet & dry	yes/no	-	-



menikini

Imported and Distributed by:



MATHIA Trading and General Cleaning Services

Headquarters: L1 B7 Dorgali St. – Pallas Athena Classique – Anabu IID - Cavite 4103 – Philippines

Tel: +63 46 418 4751 – Mobile: +63 917 507 9888

info@mathiatrading.com • www.mathiatrading.com